



- Extras de armatura - - Reinforcement Table -								
Marca	Diam. [mm]	Lungimi [m]	Bucati	Lungimea [m]				
				OB 37 Ø10	Ø10	Ø16	Ø20	Ø25
1	16	7,35	24			176,40		
2	20	7,65	24				183,60	
3	16	7,60	13			98,80		
4	16	3,05	18			48,80		
5	20	4,95	28				138,60	
6	20	3,05	24				73,20	
7	25	4,95	18					89,10
8	16	4,95	6			29,70		
9	20	7,90	11				86,90	
10	25	3,05	12					36,60
100	10	1,80	1022	1857,60				
150	10	116,8	nr		116,80			
Total Lungimi [m]				1857,6	1168,0	353,70	492,30	125,70
Masazul [kg/m]				0,617	0,617	1,578	2,466	3,853
				1145,28	72,01	558,26	1189,42	484,37
TOTAL [kg]						3450,60		

BETON / CONCRETE:

C4/5:	EGALIZARI: EQUALISATION LAYERS
C8/10:	BETON SIMPLU IN FUNDATII CONTINUE SUB ZIDURI, FUNDATII ISOLATE SUB STALPI: BLINDING CONCRETE IN CONTINUOUS OR SINGLE FOUNDATIONS:
C12/15:	BETON ARMAT IN CUZINETI, CENTURI, PLACA DE PARDOSEALA: REINFORCEMENT CONCRETE FOUNDATIONS BLOCKS, REINFORCEMENT CONCRETE BELTS, REINFORCEMENT CONCRETE GROUND SLAB
C16/20:	BETON ARMAT IN STALPI, PLANSEE, RAMPE DE SCARI: REINFORCEMENT CONCRETE IN COLUMNS, FLOORS, STAIRWAYS

OTEL / STEEL:
PC 52, OB 37

[illegible]